

Multi Manual Transmission Fluid 75W80

Description	<p>An advanced and modern multi-vehicle manual transmission fluid "MTF", based on high-quality base oils in combination with optimized additives, resulting in the following properties:</p> <ul style="list-style-type: none">- proven performance in European and Asian synchronisers- superior bearing and gear protection- excellent cleanliness- good low temperature performance- robust corrosion protection- a long durability.												
Application	<p>This multi-vehicle manual transmission oil has been specially developed for European and Asian vehicles (passenger cars and delivery vans), where the specified specifications are requested. This oil is also suitable for applications where the specified specifications are prescribed in combination with slightly different viscosities, such as 70W75, 70W90, 75W, 75W85 75W90 etc. Can also be used for dry double clutch transmissions (Dry-DCT) according to the specifications indicated. Not suitable for Wet-DCT.</p>												
Specifications	<p>Performance level:</p> <p>API GL-4</p> <p>BMW MTF LT-2 / LT-3 / LT-4</p> <p>Fiat 9.55550-MZ1 / MZ6 / MZ7</p> <p>Ford WSD-M2C200-C / WSS-M2C200-D2 / ESD-M2C186-A</p> <p>GM GMW16612 / 1940004 / 19259104</p> <p>GM 1940182 / 1940764 / 1940768</p> <p>Honda MTF / MTF-II / MTF-III</p> <p>MB 235.10</p> <p>Nissan MT-XZ / MT-XZ TL (JR Type)</p> <p>PSA B71 2310 / 2315 / 2316 / 2330</p> <p>Renault DC4 / DW5</p> <p>Special gear oil, MTF 94</p> <p>Tranself NFJ/NFP/NFX/TRJ/TRP/TRT/TRX/TRZ</p> <p>Volvo 97308 / 97309</p> <p>VW G 009 317 / 052 171 / 052 178 / 052 512</p> <p>VW G 052 527 / 052 549 / 052 726</p> <p>VW G 50 / 055 512 / 060 726 / 070 726</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,869</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>54,20</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>9,50</td></tr><tr><td>Viscosity Index</td><td>160</td></tr><tr><td>Flash Point COC, °C</td><td>222</td></tr><tr><td>Pour Point, °C</td><td>-45</td></tr></table>	Density at 15 °C, kg/l	0,869	Viscosity 40 °C, mm ² /s	54,20	Viscosity 100 °C, mm ² /s	9,50	Viscosity Index	160	Flash Point COC, °C	222	Pour Point, °C	-45
Density at 15 °C, kg/l	0,869												
Viscosity 40 °C, mm ² /s	54,20												
Viscosity 100 °C, mm ² /s	9,50												
Viscosity Index	160												
Flash Point COC, °C	222												
Pour Point, °C	-45												