

Multi ManualTransmission Fluid 75W

Description	<p>A new formula synthetic multi-vehicle transmission fluid "MTF", based on high-quality synthetic base oils in combination with optimized additives, resulting in the following properties:</p> <ul style="list-style-type: none">- proven performance in synchronisers- superior bearing and gear protection- excellent cleanliness- good low temperature performance- robust corrosion protection- a long durability.												
Application	<p>This multi-vehicle manual transmission oil has been specially developed for European and Asian vehicles (passenger cars and delivery vans), where the specified specifications are requested. This oil is also suitable for applications where the specified specifications are prescribed in combination with slightly different viscosities, such as 75W-70. Can also be used for dry double clutch transmissions (Dry-DCT) according to the specifications indicated. Not suitable for Wet-DCT.</p>												
Specifications	<p>Performance level:</p> <p>API GL-4 BMW MTF LT-3 Fiat 9.55550-MZ6 / MZ7 Ford WSS-M2C200-D2 / ESD-M2C186-A GM GMW16612 / 1940004 / 19259104 PSA B71 2310 / 2316 Tranself NFX VW G 009 317 / 052 171 / 052 178 VW G 052 512 / 052 527 / 052 549 VW G 052 726 / 055 512 / 060 726 / 070 726</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,851</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>31,80</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>6,10</td></tr><tr><td>Viscosity Index</td><td>142</td></tr><tr><td>Flash Point COC, °C</td><td>232</td></tr><tr><td>Pour Point, °C</td><td>-45</td></tr></table>	Density at 15 °C, kg/l	0,851	Viscosity 40 °C, mm ² /s	31,80	Viscosity 100 °C, mm ² /s	6,10	Viscosity Index	142	Flash Point COC, °C	232	Pour Point, °C	-45
Density at 15 °C, kg/l	0,851												
Viscosity 40 °C, mm ² /s	31,80												
Viscosity 100 °C, mm ² /s	6,10												
Viscosity Index	142												
Flash Point COC, °C	232												
Pour Point, °C	-45												