

## ATF 7G LV - CONVENTIONAL and HYBRID DRIVE

### Description

A five star high graded low viscosity automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability over lifetime ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- without dye (available in red on request).

### Application

This multi vehicle ATF with lower viscosity than conventional ATFs, can be used for automatic gearboxes of various car manufacturers, both in the low and high viscosity ATF segment that allow this. Also for hybrid applications. In addition to the specified specifications, this ATF is also applicable in certain types of automatic transmissions including: Bentley, Chrysler / Dodge / Jeep, Jaquar, Land Rover, Maserati and Porsche, for which a correspondingly low viscosity ATF is prescribed. This multi-purpose ATF also meets the hardware protection of specified ATF specifications for ultra low viscosity, but does not provide maximum fuel economy.

### Specifications

Performance level:

Aisin Warner JWS 3309/3324/AW-1/AW-2, Allison C4  
 BMW 7045E/8072B/LA2634/LT71141/ATF3/3+/6/M-1375.4  
 Chrysler ATF+ /+2/+3/+4, DTFR 13C110/140/150/170  
 Ford Mercon ULV/LV/V/SP / WSS-M2C922-A1 / M2C949-A  
 GM Dexron ULV/HP/VI/II/III/IV/TA  
 Honda DW-1/3.0/3.1/ATF-Z1 (except in CVT)  
 Hyundai/Kia SP-II/-III/-IV/-IV RR/RED-1K/NWS 9638  
 Isuzu ATF II/III, Jaguar JLM 20238/20292/21044  
 JASO M315 Type 1A LV, Mazda FZ/M-III/Type T-IV  
 MB 236.5/236.6/236.7/236.8/236.9/236.10/236.11  
 MB 236.12/236.14/236.15/236.17/236.41/236.93  
 Mitsubishi SP-II/III/J2/J3/PA, Nissan D/J/K/S/W  
 Subaru HP, Suzuki ATF 3314/3317, PSA B71 2340  
 Toyota DII/T-T-III/T-IV/WS, Volvo 1161540  
 VW G 052 025 / 052 055 / 052 162  
 VW G 052 533 / 052 990  
 VW G 055 005 / 055 025 / 055 540 / 060 162  
 ZF 11A / 11B



## ATF 7G LV - CONVENTIONAL and HYBRID DRIVE

<b>Typicals</b>	Density at 15 °C, kg/l	0,857
	Viscosity 40 °C, mm <sup>2</sup> /s	27,40
	Viscosity 100 °C, mm <sup>2</sup> /s	6,37
	Viscosity Index	197
	Flash Point COC, °C	162
	Pour Point, °C	-57