

Gear Oil Alcat 10W

Description	<p>A special premium quality oil for hydraulic and transmission equipment formulated with solvent refined base oils and selected additives to obtain the following properties:</p> <ul style="list-style-type: none">- a low pour point- a very good stability against oxidation- very good anti-wear properties, that gives a longer duration of the final drive- specific friction-properties, which grants an optimum use of the power shift transmissions- applicable in systems with "wet" brakes- excellent corrosion and foaming preventive properties																
Application	<p>This oil is special developed for the lubrication of power shift transmissions, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C4 fluid is required. This oil cannot be used in engines.</p>																
Specifications	<p>Performance level: API GL-4 Allison C4 Cat TO-4 / TO-2 Komatsu KES 07.868.1 ZF TE-ML 03C Eaton (Vickers) M-2950-S / I-286-S</p>																
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,876</td></tr><tr><td>Viscosity -25 °C, mPa.s</td><td>6460</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>43,20</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>6,50</td></tr><tr><td>Viscosity Index</td><td>101</td></tr><tr><td>Flash Point COC, °C</td><td>228</td></tr><tr><td>Pour Point, °C</td><td>-33</td></tr><tr><td>Sulphate Ash, %</td><td>0,91</td></tr></table>	Density at 15 °C, kg/l	0,876	Viscosity -25 °C, mPa.s	6460	Viscosity 40 °C, mm ² /s	43,20	Viscosity 100 °C, mm ² /s	6,50	Viscosity Index	101	Flash Point COC, °C	228	Pour Point, °C	-33	Sulphate Ash, %	0,91
Density at 15 °C, kg/l	0,876																
Viscosity -25 °C, mPa.s	6460																
Viscosity 40 °C, mm ² /s	43,20																
Viscosity 100 °C, mm ² /s	6,50																
Viscosity Index	101																
Flash Point COC, °C	228																
Pour Point, °C	-33																
Sulphate Ash, %	0,91																