



S SYNTHTURBO Ultra 15W40 TBN-16

Description	<p>A newly developed diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:</p> <ul style="list-style-type: none"> - a very powerful detergency prevents deposits in the engine - a very strong dispersion that prevents from precipitation and sludge - a powerful activity against corrosion and foam - a high and stable viscosity index - a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners. 	
Application	<p>This New and Ultra Modern engine lubricant is applicable to diesel engines (normally- or turbo-aspirated) even under tough operating conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.</p>	
Specifications	<p>Performance level: ACEA E7 API CI-4 / SL Cat ECF-1-a / ECF-2 Cummins CES 20077/20078 Detroit Diesel 93K215 Deutz DQC III-18 DTFR 15B110 Global DHD-1 JASO DH-1 Mack EO-N/EO-M Plus MAN M 3275-1 MB 228.3 MTU Type 2 Renault VI RLD-2 Volvo VDS-3 Allison C3, CAT TO-2 ZF 04C / 04P / 07C / 07D / 21K</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity -20 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Total Sulphur Content, %</p>	<p>0,87 6300 105 15,20 160 223 -30 16,1 Ultra Long Life 0,478</p>